

# SAFETY DATA SHEET

Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version 1.5      Revision Date: 11/13/2019      SDS Number: F-4624493983      Date of last issue: 03/27/2019  
Date of first issue: 07/23/2015

---

## SECTION 1. IDENTIFICATION

Product name : ALEXSEAL N9398-Interior Topcoat 9398 White Aluminium matt

Product number : 4624493983000

### Manufacturer or supplier's details

Manufacturer, importer, supplier : Mankiewicz Coatings L.L.C

Address : 1200 Charleston Regional Parkway  
Charleston, South Carolina 29492  
USA

Telephone : +1 (843) 6547755  
Telefax : +1 (843) 6547759  
E-mail address : sdb\_info@umco.de

Emergency telephone : CHEMTREC +1 (800) 4249300 or + (703) 5273887

### Recommended use of the chemical and restrictions on use

Recommended use : Industrial serial painting

---

## SECTION 2. HAZARDS IDENTIFICATION

### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

### GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

---

# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version 1.5      Revision Date: 11/13/2019      SDS Number: F-4624493983      Date of last issue: 03/27/2019  
Date of first issue: 07/23/2015

## Precautionary Statements

### Prevention:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ eye protection/ face protection.

### Response:

- P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

### Storage:

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

### Disposal:

- P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture of synthetic resins, organic solvents and pigments

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9, aromatics	64742-95-6	>= 25 - < 40
n-butyl acetate	123-86-4	>= 5 - < 12.5
aluminium	7429-90-5	>= 5 - < 12.5
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 1 - < 5
Naphtha (petroleum), hydrotreated	64742-48-9	>= 1 - < 5



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

heavy

## SECTION 4. FIRST AID MEASURES

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.  
Irregular breathing/no breathing: artificial respiration.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognised skin cleanser.  
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.  
If accidentally swallowed obtain immediate medical attention.  
Never give anything by mouth to an unconscious person.  
Keep at rest.
- Most important symptoms and effects, both acute and delayed : For information on symptoms and effects refer to Section 2 Hazard statements and Section 11 Toxicological Information.
- Notes to physician : No information available.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Further information : Cool endangered containers with water in case of fire.  
**DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!**
- Special protective equipment : As in any fire, wear self-contained breathing apparatus



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version 1.5      Revision Date: 11/13/2019      SDS Number: F-4624493983      Date of last issue: 03/27/2019  
Date of first issue: 07/23/2015

---

for fire-fighters      pressure - demand, MSHA / NIOSH (approved or equivalent) and full protective gear.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Exclude sources of ignition and ventilate the area.  
Do not inhale vapors.  
Refer to protective measures listed in sections 7 and 8.  
Evacuate personnel to safe areas.
- Environmental precautions : Do not let product enter drains.  
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.
- Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).  
Clean preferably with a detergent; avoid use of solvents.
- 

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
Preparation may charge electrostatically: always use earthing leads when transferring from one container to another.  
Operators should wear anti-static footwear and clothing. No sparking tools should be used.  
Vapors are heavier than air and may spread along floors.  
Vapors may form explosive mixtures with air.
- Advice on safe handling : Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentrations higher than the occupational exposure limits.  
Comply with the health and safety at work laws.  
Smoking, eating and drinking should be prohibited in the application area.  
Observe specific national regulations for handling and use of paints.
- Conditions for safe storage : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type.  
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- 



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
 Product No.: 4624493983000

Version 1.5      Revision Date: 11/13/2019      SDS Number: F-4624493983      Date of last issue: 03/27/2019  
 Date of first issue: 07/23/2015

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.  
 Keep container dry in a cool, well-ventilated place.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 41 - 95 °F / 5 - 35 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-butyl acetate	123-86-4	TWA	50 ppm	CR OEL
		Further information: Eye irritation, Upper Respiratory Tract irritation		
		STEL	150 ppm	CR OEL
		Further information: Eye irritation, Upper Respiratory Tract irritation		
		TWA	150 ppm 713 mg/m3	CA AB OEL
		STEL	200 ppm 950 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	150 ppm 713 mg/m3	CA QC OEL
		STEV	200 ppm 950 mg/m3	CA QC OEL
		VLE-PPT	150 ppm	NOM-010-STPS-2014
		VLE-CT	200 ppm	NOM-010-STPS-2014
		TWA	150 ppm 710 mg/m3	NIOSH REL
		ST	200 ppm 950 mg/m3	NIOSH REL
		TWA	150 ppm 710 mg/m3	OSHA Z-1
		TWA	150 ppm 710 mg/m3	OSHA P0
		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
 Product No.: 4624493983000

Version 1.5      Revision Date: 11/13/2019      SDS Number: F-4624493983      Date of last issue: 03/27/2019  
 Date of first issue: 07/23/2015

aluminium	7429-90-5	STEL TWA (Respirable fraction)	150 ppm 1 mg/m3 (Aluminum)	ACGIH CR OEL
Further information: Not classifiable as a human carcinogen, Neurotoxicity, Upper Respiratory Tract irritation, Pneumoconiosis				
		TWA (Dust)	10 mg/m3	CA AB OEL
		TWAEV	10 mg/m3	CA QC OEL
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
		TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWAEV (Welding fumes)	5 mg/m3 (Aluminum)	CA QC OEL

**Engineering measures** : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapors concentration below the OEL, suitable respiratory protection must be worn.

**Personal protective equipment**

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use MSHA/NIOSH approved respirator if concentration exceeds recommended exposure levels. Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapor. If possible, machine employing a wet medium. Where practicable, install exhaust hoods to improve capture of vapors and fumes and avoid exposition; otherwise wear respiratory protection equipment.

Hand protection

**Remarks** : Glove permeation data does not exist for this material. The following glove(s) should be used for splash protection only:



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

- Appropriate material: nitrile
- Eye protection : Use safety glasses or face shield (ANSI Z87.1 or approved equivalent).
- Skin and body protection : Personal should wear protective clothing as necessary to prevent skin contact. All parts of the body should be washed after contact.
- Protective measures : Do not eat or drink during work - no smoking.  
Avoid product contact with skin, eyes and clothing.  
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapor in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : according product name
- Odor : characteristic
- Boiling point/boiling range : ca. 248 °F / 120 °C
- Flash point : 82 °F / 28 °C  
Method: ISO 13736
- Upper explosion limit / Upper flammability limit : 10 %(V)
- Lower explosion limit / Lower flammability limit : 1 %(V)
- Vapor pressure : ca. 100 hPa (122 °F / 50 °C)
- Density : ca. 11.27 lb/gal (1.35 g/cm<sup>3</sup>)  
(68 °F / 20 °C)



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

Solubility(ies)  
Water solubility : insoluble

Autoignition temperature : > 752 °F / > 400 °C

Viscosity  
Viscosity, kinematic : 21 mm<sup>2</sup>/s (104 °F / 40 °C)  
406 mm<sup>2</sup>/s (73 °F / 23 °C)

Flow time : 91 s  
Cross section: 4 mm  
Method: DIN 53211

61 s  
Cross section: 6 mm  
Method: ISO 2431

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use. There are no data available on the preparation itself.

Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).

Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.

Hazardous decomposition products : When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Carcinogenicity

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### OSHA

No component of this product present at levels greater than or equal to 0.1% is





# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## Further information

### Product:

Remarks : Exposure of vapor concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

#### Components:

#### Hydrocarbons, C9, aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 3.2 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 2.9  
plants : mg/l  
Exposure time: 72 h



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

Method: OECD Test Guideline 201

## Solvent naphtha (petroleum), light arom.:

- Toxicity to fish : (Fish): 9.2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 3.2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes
- Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 2.6 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

## Persistence and degradability

### Product:

- Biodegradability : Remarks: There are no data available on the preparation itself.

## Bioaccumulative potential

### Product:

- Bioaccumulation : Remarks: There are no data available on the preparation itself.

## Mobility in soil

### Product:

- Mobility : Remarks: There are no data available on the preparation itself.

## Other adverse effects

### Product:

- Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

- Additional ecological information : There are no data available on the preparation itself.



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

mation

The product should not be allowed to enter drains or water courses.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : Class 3 - Flammable liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

#### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT  
(Hydrocarbons, C9, aromatics, Solvent naphtha (petroleum), light arom.)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : Class 3 - Flammable liquids  
Marine pollutant : yes(Hydrocarbons, C9, aromatics, Solvent naphtha (petrole-



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version 1.5      Revision Date: 11/13/2019      SDS Number: F-4624493983      Date of last issue: 03/27/2019  
Date of first issue: 07/23/2015

um), light arom.)

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

Components	CAS-No.	Component TPQ (lbs)
<b>SARA 311/312 Hazards</b>	: Fire Hazard Acute Health Hazard	
<b>SARA 313</b>	: The following components are subject to reporting levels established by SARA Title III, Section 313:	
	aluminium	7429-90-5      7.7999 %

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).  
This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).  
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

n-butyl acetate      123-86-4      >= 10 - < 20 %

### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

n-butyl acetate      123-86-4      12.4799 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

n-butyl acetate      123-86-4      12.4799 %

### US State Regulations

#### Massachusetts Right To Know

n-butyl acetate      123-86-4  
aluminium      7429-90-5

#### Pennsylvania Right To Know

Hydrocarbons, C9, aromatics      64742-95-6  
n-butyl acetate      123-86-4  
aluminium      7429-90-5



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

Solvent naphtha (petroleum), light arom.	64742-95-6
Naphtha (petroleum), hydrotreated heavy	64742-48-9

### Maine Chemicals of High Concern

Product does not contain any listed chemicals

### Vermont Chemicals of High Concern

ethane-1,2-diol	107-21-1
-----------------	----------

### Washington Chemicals of High Concern

ethane-1,2-diol	107-21-1
-----------------	----------

### California Prop. 65

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.  
This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### California List of Hazardous Substances

n-butyl acetate	123-86-4
aluminium	7429-90-5

### California Permissible Exposure Limits for Chemical Contaminants

n-butyl acetate	123-86-4
-----------------	----------

### The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

### TSCA list

Not relevant



# SAFETY DATA SHEET


Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version 1.5      Revision Date: 11/13/2019      SDS Number: F-4624493983      Date of last issue: 03/27/2019  
Date of first issue: 07/23/2015

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	0
FLAMMABILITY	3
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Health  
0=Slightly Hazardous Slightly Hazardous  
2=Hazardous  
3=Extreme danger  
4=Deadly

Flammability  
0=Will not burn  
2=Flashpoint below 200 F  
3=Flashpoint below 100 F  
4=Flashpoint below 73 F

Instability  
0=Stable  
1=Unstable if heated  
2=Violent chemical reaction; water reactive  
3=Shock or heat may detonate  
4=May detonate

Special hazard  
SA Simple Asphyxiant  
ACID Acid  
OX Oxidizer  
W Water Reactive  
CORR Corrosive

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

CR OEL : Costa Rica. Maximum allowable occupational exposure limits in the workplace.

NIOSH REL : USA. NIOSH Recommended Exposure Limits  
NOM-010-STPS-2014 : Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA AB OEL / STEL : 15-minute occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA QC OEL / TWAEV : Time-weighted average exposure value  
CA QC OEL / STEV : Short-term exposure value  
CR OEL / TWA : Time weighted average 8-hr value  
CR OEL / STEL : Short term exposure limit  
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

NOM-010-STPS-2014 / VLE- : Time weighted average limit value  
PPT

NOM-010-STPS-2014 / VLE- : Short term exposure limit value  
CT

OSHA P0 / TWA : 8-hour time weighted average  
OSHA P0 / STEL : Short-term exposure limit  
OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse)



# SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL N9398-Interior Topcoat  
Product No.: 4624493983000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2019
1.5	11/13/2019	F-4624493983	Date of first issue: 07/23/2015

Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/13/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8

