

Safety Data Sheet

LAT-TS1; LAT-TS32

Date Prepared: 04/26/2017

Section 1. Identification

Manufacturer:

Lat 26°

205 SW 30th Street

Fort Lauderdale, FL 33315

754-206-2356 – Office

954-588-4408 – 2nd contact

For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

1-800-424-9300 / +1 703-527-3887 CCN815696

Product Identification: LAT 26 Teak Sealer

Suggested Use: Use to seal and protect teak and other wood surfaces from exposure to environmental elements.

Section 2. Hazard(s) Identification

**Hazard Class &
Category Codes**

Hazard Statement Codes

**Pictograms &
Signal Word**

Skin Irrit. 2

H315: Causes skin irritation.



Eye Dam. 1

H318: Causes serious eye damage.

Warning

**Precautionary
Statements Codes**

Precautionary Statements

P101

If medical advice is needed, have product container or label at hand

P102

Keep out of reach of children

P103

Read label before use

P264

Wash skin thoroughly after handling.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352

IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338+P313

IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If concerned, get medical advice.

P405

Store locked up

P501

Dispose of contents/container in accordance with local/regional/national/international regulations

Section 3. Composition/Information on Ingredients

Component Name	CAS Number	EC Number	Percentage
Water	7732-18-5	231-791-2	Balance
Silicone Emulsion	Proprietary	Proprietary	18-20%

Section 4. First Aid Measures

Eyes: Flood with large amounts water at least 20 min.; get immediate medical attention if irritation persists. Can cause irritation, redness, tearing, and blurred vision.

Skin: Flush exposed area with water. Remove all contaminated clothing. Prolonged or repeated contact can cause moderate irritation.

Inhalation: If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, calm, and get medical attention.

Oral: If swallowed, induce vomiting. Vomiting can be induced with syrup of Ipecac. Give fluids until the vomitus is clear. Get medical attention.

Section 5. Fire Fighting Measures

Flash Point: 215°F

Autoignition Temperature: Not determined

Flammability Limits in Air: Not determined

Extinguishing Media: Carbon dioxide (CO₂) water spray. Dry chemical foam can be used to cool fire-exposed containers.

Fire Fighting Procedure: Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Evacuate area in case of overheating or fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Static electricity will accumulate and may ignite vapors.

Hazardous Decomposition Products: May form toxic material, carbon dioxide, carbon monoxide, various hydrocarbons, etc.

Section 6. Accidental Release Measures

Containment/Clean Up: Sections 13 and 15 of this MSDS provide information regarding certain Federal and local requirements. Collect for disposal. Clean up remaining materials from spill with suitable absorbent. For large spills provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean area as appropriate as some silicone material, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Observe all personal protection equipment recommendations described in Sections 5 and 8 of this MSDS. Observe all Federal and government regulations that may apply to the cleanup of this material.

Section 7: Handling and Storage

Handling (Personnel): Avoid contact with strong oxidizing agents. Spilled substance increases risk of slippage.

Storage: Keep container tightly closed.

Section 8: Exposure Controls and Personal Protection

Engineering Controls:

Local Exhaust: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

General exhaust: Recommended

Personal Protective Equipment for Routine Handling:

Eyes: Use proper protection – safety glasses as a minimum.

Skin: Washing at meal time and end of shift is adequate.

Suitable Gloves: butyl rubber protection gloves

Inhalation: If spraying or other operations that generate an aerosol mist are conducted, respiratory protection for exposed personnel is recommended.

Precautionary Measures: Avoid eye contact.

Section 9: Physical and Chemical Properties:

Physical Form: Liquid

Color: Opaque White

Odor: Cypress Wood

Specific Gravity @ 25C: 0.865 Soluble

Solubility in Water: VOC content (% by weight) 0%

Viscosity: 145 mm²/s

Melting Point: Not determined

Boiling Point: Not determined

Flash Point: 215° F

Vapor Pressure @ 25° C Not determined

pH: 6-7.5

Section 10: Stability and Reactivity

Chemical Stability: Stable

Hazardous Polymerization: Will not polymerize

Conditions to Avoid: None known

Materials to Avoid: Strong oxidizing agents.

Section 11: Toxicological Information

Acute Toxicity: Irritation to eyes and skin

Chronic: Unknown

Eyes: No data available

Skin: No data available

Sensitization: Not a known sensitizer

Mutagenicity: No evidence for mutagenicity

Carcinogenicity: Contains no ingredients classified as carcinogens by IARC, NTP or OSHA

Reproductive Toxicity: No known reproductive toxicity

Target Organs: None known

Aspiration Hazard: No data available

Section 12: Ecological Information

Fish: No data available

Daphnia: No data available

Algae: No data available

Section 13: Disposal Considerations

Landfill and/or incinerate where permitted in compliance with all applicable Federal, State and local government regulations.

Section 14: Transportation Information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

Section 15: Regulatory Information

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA inventory of chemical substances.

EPA SARA Title III	Section 302 Extremely Hazardous	None	
Chemical Listings	Substances		
	Section 304 CERCLA Hazardous	None	
	Substances		
	Section 312 Hazard Class	Acute	No
		Chronic	No
		Fire	No
		Pressure	No
		Reactive	No
	Section 313 Toxic Chemicals	None	

Supplemental State
Compliance
Information

Section 16: Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. Any material supplied is the sole

responsibility of the user. All materials may present unknown health hazards and we cannot guarantee that the hazards listed herein are the only hazards that exist.